

ELEMENTS INSTALLATION PROCEDURES



STOP! PLEASE READ BEFORE INSTALLING!

Be sure to always follow all OSHA regulations and common workplace safety procedures.

Shipping

To ensure that damages do not occur please follow these instructions when transporting, loading, or unloading Harmony Elements:

- **DO NOT** ship Harmony Elements without a pallet banded underneath them.
- **DO NOT** allow Harmony Elements to touch each other when transporting more than one unit.
- **DO NOT** take Harmony Elements off the pallet they are banded to until it is brought as close as possible to the intended install location.
- **TAKE YOUR TIME! UNITS ARE FRAGILE!**

CAUTION: Harmony Outdoor Living Elements are very heavy items and can be damaged by not taking the time to move them cautiously. Chipping or cracking of block can occur if these directions are not followed closely.

Installation

To ensure that block is not chipped or cracked when placing the Harmony Element please follow these instructions:

1. After the Harmony Element has been moved near its intended location, pallet banding and plastic may be removed. **CAUTION: DO NOT remove the banding that is holding the edge protectors located in the fork holes. (Not applicable to all Elements.)**
2. At this point you are ready to pick up the unit with the appropriate sized piece of equipment to move it. Be sure to check your equipment's Owner's Manual for weight capacity before lifting and moving Harmony Elements. **CAUTION: Failure to have properly sized equipment may result in dropping or damaging the Harmony Element and may cause injury to the operator.**
3. Line up the forks with the fork channel openings located on the Harmony Element unit. **CAUTION: Take your time during this process; damage can easily occur if not careful!** Once you have lined up the forks **slowly** drive the forks all the way through the unit until they come through on the opposite side of the Harmony Element.

ELEMENTS INSTALLATION PROCEDURES

4. At this point secure a strap around the entire Harmony Element to the piece of equipment that is going to move it. This will ensure that the Harmony Element does not tip off the forks while it is being moved.
5. Be sure to pick up the Harmony Element as **level** as possible at all times. After it is lifted off the pallet tilt the unit slightly back toward the equipment that is moving it.
6. **Slowly** and **carefully** place the Harmony Element in the intended location. **CAUTION: Make sure all installers keep a safe distance while the Element is being placed.**
7. Once you have placed the Harmony Element at its final install location you may undo the strap that was used to secure the Harmony Element to the equipment.
8. **Lower** the forks and **slowly** back the equipment out of the fork channels to ensure that no damage will be done to the fork channel openings.
9. You may now remove the banding and edge protectors from the fork channels. *(If applicable.)*
10. Place matching brick plugs (included) into the channel openings on the Harmony Element. **(Be careful to do this slowly so that you do not push the plugs all the way through and past the opening. It will be very difficult to retrieve the plug if it is pushed all the way through.)**

Installing Fireplace Top or Brick Oven Top

When installing the top unit of a fireplace or brick oven, please follow the instructions as outlined above. However, please add these additional instructions:

1. Before moving the top unit of a fireplace, remove the flue pipe that is shipped inside the unit. Failure to do so may result in the pipe being crushed or damaged. Note: the brick oven pipe and cap are already installed within the top unit.
2. After the fireplace or brick oven base has been properly set in place, measure and mark with a pencil where the top unit will be placed so that it sits squarely and centered both ways on the base unit.
3. When lifting the top unit **take your time** and position yourself to be as square to the base unit as possible so that only minor adjustments will need to be made to line up with the pencil lines from step one.

Installing Fireplace Flue Pipe and Termination Cap

After a Harmony Fireplace has been placed it is necessary to install the flue pipe and termination cap to complete the install. **CAUTION: Use a ladder during flue pipe and termination cap installation.** Install the flue pipe that comes with your fireplace unit. To do so, simply slide the flared end of the flue pipe through the top opening and line the pipe up with the opening in the base unit of the fireplace. Note: there may be one or two pieces of pipe with your fireplace unit. Follow the same procedure for the second piece (if applicable). Push down and snap the pipe into place. The final step is to install the termination cap by sliding it into the flue pipe. It is not necessary to fasten the termination cap to the flue pipe. Installation is now complete and ready for use.

For more information, comments, questions, or concerns please contact us at 262-539-4444.